

China Starwin 0.6M KA BAND ANTENNA DATASHEET

0.60 m Ka band antenna appearance



General description

China Starwin 0.6 m Ka band antenna delivers exceptional high performance for transmit/receive application with high gain, low noise and low interference.

China Starwin 0.6 m Ka band antenna offers a fine reflector with a stretch formed panels and effective feeder. The standard designed azimuth over elevation pedestal provides a cost-effective solution for ground or roof installation with high stiffness, stability and good wind resistance.

The electrical performance is compliant with FCC and ITU-RS-580 sidelobe specifications and Intelsat, Eutelsat, SES, AsiaSat, ChinaSat, etc requirement.

Technical Specification

Item No.	SWKA60-CP2 (Starwin 0.60m Ka band antenna)	
Antenna Diameter	0.6 m	
Antenna Type	Offset	
Antenna Pedestal Type	Kingpost	
Antenna Drive Mode	Manual	
Frequency Range	Tx : 28GHz~31GHz	Rx : 18.2 GHz~21.0GHz
Gain (midband)	Tx : $G \geq 41.0 + 20\lg(f/29.5)$	Rx : $G \geq 38.0 + 20\lg(f/19.95)$
VSWR	$\leq 1.25:1$	

China Starwin Science&Technology Co., Ltd.

Tel:+8629-87650669, E-mail:sales@starwincom.com, <http://www.starwincom.com>

Copyright©2016 Starwin

Polarization	Circular or Liner
First Sidelobe	≤ -14.5 dB
Feed Interface	Rx port: WR42, Tx port: WR28
Driving range	Azimuth: $\pm 85^\circ$ under Elevation : $5^\circ \sim +85^\circ$
Operation Wind Speed	28 m/s
Working Temperature	$-40^\circ\text{C} \sim +70^\circ\text{C}$ (outdoor)