

## China Starwin 0.75 M KA BAND ANTENNA DATASHEET

### 0.75m Ka band antenna appearance



### General description

China Starwin 0.75 m Ka band antenna delivers exceptional high performance for transmit/receive application with high gain, low noise and low any interference.

China Starwin 0.75 m Ka band antenna offers a fine reflector with a stretch formed panels and effective feeder. The standard designed azimuth over elevation pedestal provides a cost-effective solution for ground or roof installation with high stiffness, stability and good wind resistance.

The electrical performance is compliant with FCC and ITU-RS-580 sidelobe specifications and Intelsat , Eutelsat, SES, AsiaSat, ChinaSat, etc requirement.

### Technical Specification

Item No.	SWKA75-CP2 (Starwin 0.75m Ka band antenna)
Antenna Diameter	0.75m
Antenna Type	Offset
Antenna Pedestal Type	Kingpost

**China Starwin Science&Technology Co., Ltd.**

Tel:+8629-87650669,E-mail:[sales@starwincom.com](mailto:sales@starwincom.com),<http://www.starwincom.com>

**Copyright©2016 Starwin**

Antenna Drive Mode	Manual
Frequency Range	Tx : 28GHz~31GHz      Rx : 18.2 GHz~21.0GHz
Antenna Gain (dBi)	Tx : $G \geq 44.0 + 20 \lg(f/29.5)$ Rx : $G \geq 41.0 + 20 \lg(f/19.95)$
VSWR	$\leq 1.25:1$
Polarization	Circular or Liner
First Sidelobe	$\leq -14.5$ dB
Feed Interface	Rx port: WR42, Tx port: WR28
Driving range	Azimuth: $\pm 85^\circ$ under Elevation : $5^\circ \sim +85^\circ$
Operation Wind Speed	28 m/s
Working Temperature	$-40^\circ\text{C} \sim +70^\circ\text{C}$ (outdoor)